

1.112.4

Configure Linux as a PPP client

Weight 3

Linux Professional Institute Certification — 102

Nick Urbanik <nicku@nicku.org>

This document Licensed under GPL—see section 16

2005 October

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: chat
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

pppd options

Other methods of
authentication

ISDN

ADSL

ip-up, ip-down

Troubleshooting
Connections

License Of This
Document

Outline

Context
Objectives
What is PPP?
PPP Clients and Servers
Overview of PPP connection
Establishing the serial
connection: `chat` scripts
 An example `chat` script
 Using `wvdial` to dial
Flow Control
Names of serial ports in Linux
systems

Speed of data
`pppd` options
 Where are the options
 put?
 The options
Other methods of
authentication
ISDN
ADSL
`ip-up`, `ip-down`
Troubleshooting Connections
License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topic 112 Networking Fundamentals [14]

Where we are up to

- 1.112.1 Fundamentals of TCP/IP [4]
- 1.112.3 TCP/IP configuration and troubleshooting [7]
- 1.112.4 **Configure Linux as a PPP client [3]**

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Description of Objective

1.112.4 Configure Linux as a PPP client [3]

Candidates should understand the basics of the PPP protocol and be able to configure and use PPP for outbound connections. This objective includes the definition of the chat sequence to connect (given a login example) and the setup commands to be run automatically when a PPP connection is made. It also includes initialisation and termination of a PPP connection, with a modem, ISDN or ADSL and setting PPP to automatically reconnect if disconnected.

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: chat
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

pppd options

Other methods of
authentication

ISDN

ADSL

ip-up, ip-down

Troubleshooting
Connections

License Of This
Document

Key files, terms, and utilities include:

1.112.4 Configure Linux as a PPP client [3]

`/etc/ppp/options.*` — main configuration file
for `pppd`

`/etc/ppp/peers/*` — allow users to use
privileged options configured by the
administrator

`/etc/wvdial.conf` — configuration for the
`wvdial` dialer

`/etc/ppp/ip-up` — script executed when PPP
connection made

`/etc/ppp/ip-down` — script executed when PPP
connection terminates

`wvdial` — a PPP dialer

`pppd` — The daemon that implements the
PPP protocol

What is PPP?

- ▶ The Point-to-Point Protocol (PPP) provides a connection between two systems using a serial interface.
- ▶ Usually used with ADSL, a dial-up modem, or ISDN modem
- ▶ Can also use over a direct connection called a *null modem*
- ▶ I have often used PPP over a secure shell connection to create a tunnel over SSH
- ▶ Creates a new network interface: first is called `ppp0`, next one is `ppp1`,...
- ▶ Kernel needs to support PPP, but I have found no recent desktop distributions that do not provide compiled-in support for PPP.

PPP Clients and Servers

- ▶ The same software — `pppd` — is used both for PPP dialup clients and PPP servers.
- ▶ A server simply uses software like `mgetty` to answer a modem, and an `/etc/inittab` entry like:
`S1:2345:respawn:/sbin/mgetty ttyS1`
... with some setup in
`/etc/mgetty+sendfax/mgetty.config`
- ▶ However, the LPI objectives only include use of Linux as a client.

Overview of PPP connection

1. Client connects to server through a serial connection
2. Client authenticates to the server.
3. PPP starts on the client
4. PPP server usually provides address to client; client and server agree on various other parameters
5. client configures its network interface using information provided by the server, often including a default route.

Establishing the serial connection: chat scripts

- ▶ Much of the work in establishing the PPP connection is getting the modem to dial and talk with the other end.
- ▶ We use a program called `chat`, configured by a
- ▶ *chat script* for this, and also possibly for logging in, and sometimes starting PPP.
- ▶ Questions about chat scripts seem to appear in LPIC exams.

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: chat
scripts

An example chat script
Using `wvdial` to dial

Flow Control

Names of serial ports
in Linux systems

Speed of data

pppd options

Other methods of
authentication

ISDN

ADSL

ip-up, ip-down

Troubleshooting
Connections

License Of This

Outline

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection:

`chat` **scripts**

An example `chat` **script**

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
`scripts`

An example `chat` **script**
Using `wvdial` to dial

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This

An example chat script

- Consists of pairs of *expected response* then *string sent*

```
ABORT BUSY
ABORT ERROR
ABORT 'NO CARRIER'
ABORT 'Invalid Login'
ABORT 'Login Incorrect'
'' ATZ
OK ATDT95672314
CONNECT ''
ogin: nicku
ssword: <password>
TIMEOUT 5
> ppp
```

What chat sees

- ▶ The `chat` script above was written for a session that looked like this:

```
ATZ
```

```
OK
```

```
ATDT95672314
```

```
CONNECT 31200/ARQ/LAPM/V42BIS
```

```
User Access Verification
```

```
login:nicku
```

```
Password: <password>
```

```
msusw2>ppp
```

```
Entering PPP mode.
```

```
...
```

Outline

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection:

`chat` **scripts**

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

An example `chat` script
Using `wvdial` to dial

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This

Using `wvdial` to dial

- ▶ The `wvdial` program helps simplify the connection
- ▶ The program `wvdialconf` helps write a configuration file `~/.wvdialrc` or `/etc/wvdial.conf` which may need minor tweaking to use with `pppd`
- ▶ You can then use `wvdial` to dial the server, call `pppd` and handle the authentication
- ▶ In Ubuntu Hoary, I found this the simplest way to set up the use of PPP.

Flow Control

- ▶ A serial interface has a buffer which, when full, cannot accept more information
- ▶ Any more information received is lost
- ▶ Flow control is a way to stop this happening before the buffer is full
- ▶ There are two methods of flow control:

hardware flow control uses two standard serial control lines: `ready-to-send` (RTS) and *clear-to-send* (CTS)

- ▶ enabled with `pppd` using the option `crtcts`

software flow control uses two characters: `XON` and `XOFF` to send flow control information mixed with the data

- ▶ less efficient than hardware flow control

Names of serial ports in Linux systems

- ▶ The first serial port is `/dev/ttyS0`, the second is `/dev/ttyS1`,...
- ▶ Ancient text books, or ignorant authors of new books using obsolete sources :-) may refer to serial ports as `/dev/cua0`, `/dev/cua1`,...

Speed of data

- ▶ Compression allows the flow of data in and out of a modem to exceed the maximum speed of transmission over the phone line by a factor of four
 - ▶ so set the serial speed higher than the modem is capable of transmitting
- ▶ The speed of data transfer over a serial link is measured in bits per second (bps)
- ▶ The term “*baud*” is not the same as “bits per second”
 - ▶ baud is a measure of symbols per second. If there is only one bit per symbol, then baud = bit rate, but usually they are different
 - ▶ All the same, much confusion exists, and in `wvdial.conf`, the speed in bits per second is set using an option “Baud”.

Outline

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection:

`chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This

pppd options

- ▶ `pppd` options are set:
 - ▶ in `/etc/ppp/options`
 - ▶ in `/etc/ppp/peers/*`
 - ▶ Enables ordinary users to use options otherwise disallowed by non-`root` users
 - ▶ on the command line of `pppd`

1.112.4

Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This

Outline

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection:

`chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This

Frequently used options

`asynctmap` *<map>* — specifies which control characters (ASCII characters lower than space) will be sent as a two-byte escape sequence; usually, need this to be set to zero

`connect` *<script>* — the script called before PPP protocol starts, usually `chat` *<chat-script>* to dial the number

`crtscts` — Use hardware flow control

`debug` — debugging info to syslog for troubleshooting

`defaultroute` — set up a default route via remote PPP peer

`lock` — create a lock file to get exclusive access to the serial device

`nodetach` — keep `pppd` in the foreground for debugging

`call` *<name>* — read options from `/etc/ppp/peers/name`, including privileged options

`persist` — restart the PPP connection if it fails for any reason. *Mentioned in objectives*

Other methods of authentication

The chap example above showed a client logging in responding to username/password prompts (uses `pppd` option `noauth`)

PAP — Password Authentication Protocol: started by client sending a username, password. This information is stored in a simple text file, `/etc/ppp/pap-secrets`. I have used PAP with most ISPs.

CHAP — Challenge Handshake Authentication Protocol: started by server, which sends its name and a challenge. Client responds with its name and a value derived from the challenge and its authentication information, which is stored in `/etc/ppp/chap-secrets`

MSCHAP — It will be a surprise to most that Microsoft, normally a vigorous supporter of IETF and other Internet standards, has gone out on a limb with this one, but it is a Microsoft specific version of CHAP used on MS RAS servers.

- ▶ Most ISDN modems are configured the same way as other dial-up modems.
- ▶ I configured a chat script for my parents' ISDN modem using `wvdial` on Ubuntu Hoary Hedgehog
- ▶ Main difference: the device is `/dev/ttyACM0`

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: chat
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

pppd options

Other methods of
authentication

ISDN

ADSL

ip-up, ip-down

Troubleshooting
Connections

License Of This
Document

- ▶ I use the package `rp-pppoe` from <http://www.roaringpenguin.com/pppoe/> to connect via ADSL to my Internet Service Provider (ISP)
- ▶ See the documentation with the package

ip-up, ip-down

- ▶ The script `/etc/ppp/ip-up` is executed when the PPP connection is established
- ▶ The script `/etc/ppp/ip-down` is executed when the PPP connection is disconnected
- ▶ I have used `/etc/ppp/ip-up.local` (executed from `/etc/ppp/ip-up`) to add static routes when making other PPP connections besides to my ISP
 - ▶ Also useful for telling a dynamic DNS provider that your IP address has changed
- ▶ Both are called with six parameters to let you know what IP addresses you have, ...

Troubleshooting Connections

- ▶ A *terminal program* is your best tool for troubleshooting a serial connection; examples:
 - `minicom` — the program most likely to be asked about in the exam
 - `kermit` — a more powerful terminal program that has finally been included in most modern distributions since the license was made explicitly free for Linux distributors
- ▶ Add the option `debug` to PPP options
- ▶ Add the option `-v` to `chat`
- ▶ use the option `nodetach` to keep `pppd` in the foreground
- ▶ Increase the level of detail to `debug` logged by facility `daemon` in `/etc/syslog.conf`
- ▶ Monitor the `/var/log/messages` log file

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

**Troubleshooting
Connections**

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

An example `chat` script

Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

Where are the options put?

The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

Topics Covered

Context

Objectives

What is PPP?

PPP Clients and Servers

Overview of PPP connection

Establishing the serial connection: `chat` scripts

 An example `chat` script

 Using `wvdial` to dial

Flow Control

Names of serial ports in Linux systems

Speed of data

`pppd` options

 Where are the options put?

 The options

Other methods of authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting Connections

License Of This Document

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: `chat`
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

`pppd` options

Other methods of
authentication

ISDN

ADSL

`ip-up`, `ip-down`

Troubleshooting
Connections

License Of This
Document

License Of This Document

Copyright © 2005 Nick Urbanik <nicku@nicku.org>
You can redistribute modified or unmodified copies of this document provided that this copyright notice and this permission notice are preserved on all copies under the terms of the GNU General Public License as published by the Free Software Foundation — either version 2 of the License or (at your option) any later version.

1.112.4
Configure Linux as a
PPP client
Weight 3

Nick Urbanik

Context

Objectives

What is PPP?

PPP Clients and
Servers

Overview of PPP
connection

Establishing the serial
connection: chat
scripts

Flow Control

Names of serial ports
in Linux systems

Speed of data

pppd options

Other methods of
authentication

ISDN

ADSL

ip-up, ip-down

Troubleshooting
Connections

License Of This
Document